


TECHNICAL DATA SHEET



PRODUCT:

FLUXIRTEC – R

APPLICATION:

FLUXIRTEC-R is a flux-oil used for the production of cold mix asphalts and emulsions.

FLUXIRTEC-R does not emit any unpleasant smell during the production operation and after the applications.

FLUXIRTEC-R is compatible with all the emulsifiers for emulsion production or it is melted in bitumen.

DOSAGE:

Recommended doses are

- 1-10% weight/weight in case of emulsion production
- 18-25% weight/weight on bitumen proportion in case of cold mix asphalt production.

CHEMICAL FAMILY:

FLUXIRTEC-R is an oil from petroleum refinery process.

PHYSICAL AND CHEMICAL PROPERTIES:

Appearance	Thick oil
Smell	N/A
Density at 15°C, g/cm ³	0.975±0.005
Viscosity at 100°C, cSt	75
Freezing point, °C	25
Water, % Volume	<0.1
Flash point, open cup, °C	>270

STORAGE:

Stable at room temperatures if stored in closed containers and at shadow.

PACKAGE:

FLUXIRTEC-R is delivered in 180 kg metallic drums.

SAFETY:

FLUXIRTEC-R is chemical product and should be treated with common cares. For further information, see our Material Safety Data Sheet.

The information contained herein is indicative only and without express guarantee. As no control can be exercised over its use, we cannot be held responsible for any damage which may result from its misuse