


TECHNICAL DATA SHEET



PRODUCT:

FLUXIRTEC – F

APPLICATION:

FLUXIRTEC-F is a natural vegetal flux-oil used for the production of cold mix asphalts and emulsions.

FLUXIRTEC-F due to its natural provenience does not emit any unpleasant smell during the production operation and after the applications

FLUXIRTEC-F is an environmental friend product and it is not included in the group of volatile organic compounds as well all the other product coming from oil distillation.

FLUXIRTEC-F is compatible with all the emulsifiers for emulsion production or it is melted in bitumen.

DOSAGE:

Recommended doses are

- 1-10% weight/weight in case of emulsion production
- 18-25% weight/weight on bitumen proportion in case of cold mix asphalt production.

CHEMICAL FAMILY:

FLUXIRTEC-F is a vegetal oil methylic ester

PHYSICAL AND CHEMICAL PROPERTIES:

Appearance at 20°C	Amber Liquid
Density at 25°C, g/cm ³	0.88±0.03
Flash Point °C	> 150
Viscosity at 20°C, °Engler	1,2 ± 0,1

STORAGE:

Stable at room temperatures if stored in closed containers and at shadow.

PACKAGE:

FLUXIRTEC-F is delivered in 200 metallic drums or 1000 liters plastics containers.

SAFETY:

FLUXIRTEC-F is not toxic and not dangerous for its employment. For further information, see our Material Safety Data Sheet.

The information contained herein is indicative only and without express guarantee. As no control can be exercised over its use, we cannot be held responsible for any damage which may result from its misuse