


TECHNICAL DATA SHEET


PRODUCT:

POLIRTEC 411

APPLICATION: **POLIRTEC 411** is a radial structure copolymer of styrene and butadiene used for reducing thermal susceptibility and increasing mechanical resistance of Hot Mix Asphalts.

POLIRTEC 411 is a 70/30 butadiene/styrene thermoplastic co-polymer, polymerized in solution.

POLIRTEC 411 is an excellent modifier for asphalt applications including self-adhesive roofing membrane and sealant.

DOSAGE AND APPLICATION CONDITIONS:

Dosage varies from 1% to 10% w/w on bitumen depending on the production application.

POLIRTEC 411 is normally used to produce Polymer Modified Asphalt (PMB) and membranes and it is dispersed in the bitumen using appropriate manufacturing equipment.

CHEMICAL FAMILY:

POLIRTEC 411 is 70/30 butadiene/styrene thermoplastic co-polymer, polymerized in solution and has a radial structure.

PHYSICAL AND CHEMICAL PROPERTIES:

Properties	Test method	Value
Toluene solution viscosity 5,23%	NM 300-11	28
Volatile matter, % max	ASTM D5668	0.75
Total styrene (on polymer), %	ASTM D5775	30
Insoluble matter, %max	NM 300-15	0.1

STORAGE:

Store at room temperature in closed bags. Avoid moisture.

PACKAGE:

It is presented as free flowing porous crumb making easy its handling and dissolution or in micronized powder (in this case the product assumes the denomination **POLIRTEC 411M**)

POLIRTEC 411 is delivered in 750 kg big-bags or in self-melting plastic bags.

SAFETY:

Not dangerous (According to EEC Directives)
For further information see the Safety Sheet

The information contained herein is indicative only and without express guarantee. As no control can be exercised over its use, we cannot be held responsible for any damage which may result from its misuse

international road technology consulting s.l.

C/Orquidea 12 – 28981 Parla (Madrid) – SPAIN
info@irtecon.com

Ph. +34 914132159 fax +34 915151503
www.irtecon.com