


TECHNICAL DATA SHEET



PRODUCT:

RAPIRTEC-R

APPLICATION:

RAPIRTEC-R is an additive used for rejuvenating the aged binder of the asphalt pavement during a recycling process of RAP (Reclaimed Asphalt Pavement). It reduces the stiffness of recycled asphalt allowing the using of high dosage of RAP within the mix.

RAPIRTEC-R can be used both in hot and cold systems.

It can be sprayed to the RAP during the hot mix recycling process inside the asphalt plant mixer, or it can be incorporated to the bitumen tank before starting the production process.

In case of cold processes, it can be added to the binder before the production of the due emulsion.

RAPIRTEC-R is compatible with any emulsifier for emulsion production, and it could be melted in any bitumen.

RAPIRTEC-R acts as fluxing agent, regenerator, plasticizer and antioxidant for bitumen.

DOSAGE:

Dosages depends on many factors:

- Rate of RAP within the total asphalt mix
- Characteristic of the aged bitumen
- Mix design of the asphalt mix

According to our experience, the dosage of **RAPIRTEC-R** varies between 0,20% and 0,35% of the RAP introduced in the mix.

CHEMICAL FAMILY:

RAPIRTEC-R is an oil from petroleum refinery process.

PHYSICAL AND CHEMICAL PROPERTIES:

Appearance	Thick oil
Smell	N/A
Density at 15°C, g/cm ³	0.975±0.005
Viscosity at 100°C, cSt	75
Freezing point, °C	25
Water, % Volume	<0.1
Flash point, open cup, °C	>270

STORAGE:

Stable at room temperatures if stored in closed containers and at shadow.

PACKAGE:

RAPIRTEC-R is delivered in 180 metallic drums.

SAFETY:

Chemical products should be handled with care. In order to avoid injuries, protective gloves and safety goggles should be used. For further information, see our Safety Data Sheet.

The information contained herein is indicative only and without express guarantee. As no control can be exercised over its use, we cannot be held responsible for any damage which may result from its misuse.

international road technology consulting s.l.